

FLEXIBLE, RELIABLE & HIGH PERFORMANCE POS TERMINALS & PERIPHERALS

For Enquiry

+91 953 543 2110



GT-7016-G2



- Intel TGL UP3 Core i3/i5/i7-Ultra Thin Slim Screen with latest oTP Touch
- 8GB DDR4 (Max 64GB), 128GB M.2 SSD
- Attachment Options - MSR, 2D Scanner, Secondary Screen (Touch / Non-Touch), Pole Display

BT-8016



- 15.6" oTP LCD
- Intel Raptor Lake U Core i3/i5/i7
- DDR5 SO-DIMM, max. 64GB, 128GB SSD
- Resolution -1920 x 1080, FHD
- Landscape / Portrait Kiosk mode
- Optional Inbuilt Printer & Epson TM-M30 Compatible Bracket

PS-621X



- Intel 11th Gen TGL Core i3/ i5 /i7 Processor
- 8GB DDR4L(Max 64GB), 128GB M.2 SSD
- 15.6" True-flat PCAP with multi-touch support (IP65 on front panel)

PS-3616/G2



- Intel QC/J6412
- 4GB DDR4(Max 16 GB), 128GB M.2 SSD
- Attachment Options - Secondary Screen (Touch / Non Touch), Pole Display, MSR, 2D Scanner

XT-8315



- Intel 11th Gen, Core i5/i7
- 4GB DDR4 (Max 64GB), 128GB M.2 SSD
- 15" True-flat PCAP with multi-touch support (IP65 on front panel)

XT-8317



- Intel 11th Gen Core i3/i5 /i7
- 4GB DDR4 (Max 64GB), 128GB HDD
- Options - Secondary Screen, Pole Display, MSR, 2D Scanner

HC-1621P/Pro



- Intel 7th Gen Core i3/i5 Fanfree Rugged Touch Terminal
- 8GB , Max. 32GB 128GB M.2 SSD
- Supports Win10/11 IoT, TPM & RAID Feature with Dual LAN

HC-2021A

- Android 9.0*/Android 10.0 with GMS
- Rockchip RK3399, Dual-core Cortex A72 up to 1.8GHz + Quad-core Cortex A53 up to 1.4GHz
- DDR4 4 GB, Storage 32 GB

RT-6015-G2



- Intel 11th Gen, Core i3
- 4GB DDR4 (Max 64GB), 128GB M.2 SSD
- Resolution: (RT6015) 1024 x 768 / (RT6016) FHD 1920 x 1080
- Attachment Options - MSR, 2D Scanner, Secondary Screen (Touch / Non-Touch), Pole Display

POS Peripherals




POS KEYBOARD



CASH DRAWER



BUMP BAR KEYBOARD



MSR & POLE DISPLAY



SECONDARY TOUCH MONITOR

JK Series

- 27"/32" True-flat PCAP multi-touch
- Android 10 with GMS / Windows core i3 or i5
- DDR4 SO-DIMM slot x 1, max. 32 GB, 256GB SSD
- Resolution: 1920 x 1080, Dual Side (optional)



EK Series

- 21" True-flat PCAP multi-touch
- Android 10 with GMS / Windows core i3 or i5
- DDR4 SO-DIMM slot x 1, max. 32 GB 256GB SSD
- Resolution: 1920 x 1080, table top or floor mount stand



HK Series

- 15.6" TFT PCAP multi-touch
- Android 10 with GMS / Windows core i3 or i5
- DDR4 SO-DIMM slot x 1, max. 32GB
- Resolution: 1920 x 1080, passport & ID card reader



KDS-4321

- Intel Raptor Lake U Core i3/i5/i7
- DDR5 SO-DIMM x 2, max. 64 GB
- Windows 10 IoT LTSC / Windows 11 IoT LTSC
- 21.5" True-flat PCAP touch with High-end infotainment terminal (IP65 on front panel)



TX5000 + / TX7000

- Intel 11th Gen/Intel 13th Gen Core- i3/i5/i7
- Default 8G (max 64GB, 128GB M.2 SSD)
- M.2 expansion slot
- Supports Win10/11 IoT, 9 USB Port (4 x USB 3.0+ 5 x USB 2.0), 4 Serial, Dual LAN



TX-2300-G2

- Celeron J6412, up to 2.60 GHz, 1.5M Cache M.2 128GB
- DDR4 SO-DIMM x 2, max. 32GB
- DB9 x 2 + RJ45 x 2, 5V/12V support on all COM ports
- USB 3.0 x 2 + USB 2.0 x 4



MT-6208A

- 8" Android 13 W/GMS MediaTek MT8786
- 4GB LPDDR4, 64GB eMMC (optional 8GB 128GB eMMC)
- Resolution - 1280 x 800

MT-6210A

- 10" Android 13 W/GMS MediaTek MT8786
- 4GB LPDDR4, 64GB eMMC (optional 8GB 128GB eMMC)
- Resolution - 1280 x 800

MT-6210W

- 10" Windows 11 IoT, Intel Elkhart Lake N6210
- 8GB LPDDR4, 64GB eMMC
- Resolution - 1280 x 800, 2D Barcode scanner



PP-8802/8803/7100

- Print / Paper Width - 64 mm [512 dots/line] / 72 mm [576 dots/line] / 80 or 58 +0/-1 mm
- Resolution - 8 dots/mm, up to 576 dots/line [default 512 dots/line]
- Print Speed - Up to 220 mm/sec
- Cutter - Auto cutter + manual cutter
- LED Indicator - Power; Error; Paper out

