

RLS-1000B/1000P/1000H

Thermal Label Printing Scales

- Fashionable appearance
- Support bulk import PLU by USB
- Waterproof, moisture proof, insect-resistant
- Dual-motor printing module design, more durable
- Support different size receipt paper and label paper
- With drawable printer module, convenient operation
- Multiple barcode optional, e.g. 8bit, 13bit and 18bit
- Support search PLU No. And product content by code
- Display type: double screen dot matrix display



Specification

RLS-1000B/1000P/1000H

Max Capacity	6/15kg
Verification Scale Interval	2/5g
Minimum Capacity	40g
Display	Two Line LCD 96*32 / 256*32/96*32 dot matrix display Weighting digit : 5 digit; Unit price digit : 8 digit; Total price digit : 8 digit.
Keyboard	Type: Mylar Button Number :84 buttons (28 function keys, 56*2 hot keys)/140 buttons (28 function keys, 112 hot keys)
PLU Programmable Data	LFCODE, Item name, Item No., unit price, charge unit, Fresh days, Tare Weight, barcode, department, packing weight, packing type (normal , fixed weight, fixed price, fixed weight and fixed price), Info One, Info Two, Label format, discount, hotkey.
Data Storage	Store 10000PLU, can set at most 112 hotkeys/ 112*2 hotkeys/56*2 hotkeys
Printing Speed	90mm/s
Interface	RS232+Ethernet+WiFi/Serial+ Ethernet (Wifi)/Serial+Ethernet
Power Supply	AC100~ 240V,50/60Hz
Dimension	[LxWxH] 437*372*170/437* 372 * 523/388*343*985 mm
Label Paper Size	Width: 30~60mm, Max outer diameter:100mm, Max inner Diameter: 40/28 mm
Paper Out Method	Tear or Strip
Environment Specification	Working Temperature: 0~40° C, Working Humidity: 20 - 85%/-10 - 60% Storage Temperature: - 20~70° C/5~85°C, Storage Humidity: 20-85%/10 - 90%
Accuracy Class	III
Executive Standard	GB/T 7722-2005

Solutions



Supermarket



Bakery



Fruits & Vegetables



Meat Shop